

# CUSTOM-AIR PRODUCTS

## AIR SPRINGS

Firestone air springs and accessories are the preferred choice of the street vehicle enthusiast who demands quality and ride performance. With highly engineered air springs and components, Firestone continues to provide the custom market with dependable suspension solutions.

### Air Inlet Hole Sizes

- 1/8 NPT = .33"
- 1/4 NPT = .46"
- 3/8 NPT = .58"
- 1/2 NPT = .72"
- 3/4 NPT = .92"



Use heat shields for air springs 3" from exhaust systems. Maintain a minimum of a 1/2" of clearance around the air spring while inflated. Ride Height is defined as the drive position of the vehicle. Larger port sizes are offered for increased response time.

Maximum operating pressure is 100 PSI.




### Single Convolved




#### 160BY


Min. Height 3.00"  
Max. Height 6.50"  
Ride Height 5.00"-6.00"  
Max. Diameter 7.20"



6868




6869




#### 116B-1

Min. Height 2.10"  
Max. Height 7.50"  
Ride Height 5.00"-6.00"  
Max. Diameter 9.20"




1132

### Double Convolved




#### 25C


Min. Height 2.80"  
Max. Height 7.00"  
Ride Height 4.50"-5.50"  
Max. Diameter 6.40"




6959



7687




7883




#### 267C1.5


Min. Height 2.80"  
Max. Height 8.30"  
Ride Height 5.50"-6.50"  
Max. Diameter 6.60"




6397




6781




6782




6783



6784



6786




7882

DO NOT EXCEED THE VEHICLE'S RECOMMENDED GROSS VEHICLE WEIGHT RATING (GVWR)

# CUSTOM-AIR PRODUCTS


## AIR SPRINGS

### Double Convoluted




**224C**


Min. Height 2.80"  
Max. Height 8.75"  
Ride Height 6.00"-7.00"  
Max. Diameter 8.00"




**0335**




**6836**




**6837**



**6873**




**7676**




**26C**


Min. Height 3.00"  
Max. Height 9.00"  
Ride Height 7.00"-8.00"  
Max. Diameter 8.60"



**6827**



**7325**




**7677**

### Reversible Sleeve




**1T14C1**

Min. Height 4.25"  
Max. Height 13.60"  
Ride Height 9.80"  
Max. Diameter 9.10"




**2107**



**1T14C3**

Min. Height 5.80"  
Max. Height 15.75"  
Ride Height 10.50"  
Max. Diameter 8.75"




**5405**

### Tapered Sleeve




**110 / 70**

Max. Diameter 5.70"




Min. Height 6.25"  
Max Height 10.25"  
Ride Height 8.25"

**9000**



Min. Height 4.37"  
Max Height 8.37"  
Ride Height 6.38"

**9001**



Min. Height 5.25"  
Max Height 9.25"  
Ride Height 7.25"

**9002**

DO NOT EXCEED THE VEHICLE'S RECOMMENDED GROSS VEHICLE WEIGHT RATING (GVWR)